



MATERIAL SAFETY DATA SHEET

Schnee-Morehead®, Inc.

SECTION I - IDENTIFICATION

PRODUCT NAME : Pro Installer 4300

PRODUCT CODE : 4300

DESCRIPTION : Polyurethane Foam Sealant

HAZARDOUS CLASSIFICATION: 2.1

PROPER SHIPPING NAME : Aerosols, Flammable, N.O.S., diethyl ether

SHIPPING DESCRIPTION : Aerosols, Flammable, N.O.S., diethyl ether, UN 1950

H.M.I.S RATINGS:

H	F	R	P
2	4	3	G

SECTION II - MANUFACTURER

MANUFACTURER'S NAME : Schnee-Morehead, Inc.

STREET ADDRESS : 111 North Nursery Road, Irving, Texas

INFORMATION PHONE : 972-438-9111

EMERGENCY PHONE : 800-424-9300

DATE PREPARED : August 14, 2006

SUPERSEDES DATE : January 8, 2004

SECTION III - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT (WGT)
Polymeric Diphenylmethane diisocyanate	9016-87-9	N.A.	N.A.	N.A.	30-60
Butane	106-97-8	N.A.	800 ppm TWA	N.A.	< 10
Propane	74-98-6	1000 ppm TWA	2500 ppm TWA	N.A.	< 10

SECTION IV - PHYSICAL PROPERTIES

SPECIFIC GRAVITY (H₂O=1) : 1.01

BOILING POINT : N.A.

NONVOLATILE (% WEIGHT) : N.A.

MELT/FREEZE PT : N/A

SOLUBILITY IN WATER : Insoluble

VAPOR DENSITY : N.A.

EVAPORATION RATE (BuAc=1) : N.A.

VAPOR PRESSURE : N.A.

VOLATILE ORGANIC CONTENT : N.A.

APPEARANCE/ODOR : Aerosol, foams upon release, tan color with amine like odor.

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : < 32°F

METHOD USED : N.A.

FLAMMABLE LIMITS IN AIR BY VOLUME LOWER : 4%

UPPER : 8%

EXTINGUISHING MEDIA : Use carbon dioxide, dry chemical, foam or fog.

SPECIAL FIREFIGHTING PROCEDURES : Firefighters should wear a self contained breathing apparatus and full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARD : Uncured product contains diphenylmethane-4,4 diisocyanate that can cause allergic reaction to the skin. Inhalation of the vapor may result in respiratory allergies. Propellants are extremely flammable. Pressure in container rises with heating. If container is heated, the container could burst.

SECTION VI - REACTIVITY DATA

STABILITY : Reaction at high temperature may be violent.

CONDITIONS TO AVOID : Avoid heat and do not expose to temperatures exceeding 120°F. Store in a cool dry location in closed packing at temperatures below 120°F. Keep ignition sources away - DO NOT SMOKE. Protect against electrostatic charges. Pressurized container: protect from sunlight.

INCOMPATIBILITY (MATERIALS TO AVOID) : Avoid contact with strong caustics, amines, alkali metal compounds, alcohols and water.



MATERIAL SAFETY DATA SHEET

Schnee-Morehead[®], Inc.

SECTION XI - DISCLAIMER

This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

A MSDS such as this cannot be expected to cover all possible individual situations. The end user of this product has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where, precautions – in addition to those described herein – are required. Any health and safety information contained herein should be passed on to your customers and/or employees.

The opinions expressed herein are those of qualified experts within Schnee-Morehead[®], Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the use of this product are not within the control of Schnee-Morehead[®], Inc., final determination of suitability of this product is the sole responsibility of the user. It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

=====
N/A = Not Applicable, N.A. = Not Available, N.D. = Not Determined, N/E = Not established, UNK = Unknown